ENF FORM -65A: OPERATIONS AND MAINTENANCE DAILY CHECKLIST (PERC)

Component	ATCM Requirement	Week of/						
		1	2	3	4	5	6	7
Refrigerated Vapor Condenser	Air outlet temp. must be at or below 45°F or 7°C during cool down (record temp).							
Button and Lint Traps	Clean traps every day and place lint in tightly sealed containers.							
Component	ATCM Requirement		Week of / /					
	- 3."	1	2	3	4	5	6	7
Refrigerated Vapor Condenser	Air outlet temp. must be at or below 45°F or 7°C during cool down (record temp).							
Button and Lint Traps	Clean traps every day and place lint in tightly sealed containers.							
	·	_						
Component	ATCM Requirement	1	2	Week of _	4	<u>/</u> 5	6	7
Refrigerated Vapor Condenser	Air outlet temp. must be at or below 45°F or 7°C during cool down (record temp).			3	7		U	,
Button and Lint Traps	Clean traps every day and place lint in tightly sealed containers.							
		_						
Component	ATCM Requirement	1	2	Week of _	<u>/</u>	<u>/</u> 5	6	7
Refrigerated Vapor Condenser	Air outlet temp. must be at or below 45°F or 7°C during cool down (record temp).	1	2	3	4	3	0	/
Button and Lint Traps	Clean traps every day and place lint in tightly sealed containers.							