

## Information Required with PTO Application (ver 1.3)

The following test results on approved data forms must be submitted with PTO applications (see your ATC permit and the applicable ARB Executive Order for site specific requirements). Please use the check boxes to ensure that all test results have been submitted along with your PTO. <sup>1</sup>

- Static Leak Decay Test (TP-201.3)
- Vapor-to-Liquid Ratio Test (Exhibit 5 of Executive Order)
- Leak Rate and Cracking Pressure of Pressure/Vacuum Vent Valves (TP-201.1E) <sup>2</sup>
- Static Torque of Phase I Adapters (TP-201-1B)
- Pressure Integrity Test of Drop Tube/Drain Valve Assembly (TP-201.1 C/D)
- Static Pressure Performance of Healy Clean Air Separator (Exhibit 4)
- Healy Positive Pressure Leak Check Test (Side A) and Vacuum Integrity Test (Side B)
- Dynamic Back Pressure Test (TP-201.4)

\\sbcapcd.org\shares\groups\enr\wp\gdf\gdfptotestdata.doc

Terence E. Dressler · Air Pollution Control Officer  
260 North San Antonio Road, Suite A · Santa Barbara, CA · 93110 · www.sbcapcd.org · 805.961.8800 · 961.8801 (fax)

<sup>1</sup> SBCAPCD does not require the Healy Nozzle Bag Test Procedure or the Pre-Backfill Blockage Test.

<sup>2</sup> Only required for new or rebuilt stations.